

# Technical data sheet

## Wiring trunking BE-DIN 37.5, trunking width 37.5

Item number: 6132355



Wiring trunking for horizontal and vertical routing in the switchgear cabinet. Direct mounting on the wall with double-sided adhesive tape or via the integrated base perforation. Flame-retardant and self-extinguishing after removal of an active flame. The retainers in the trunking base can be broken out without tools. Tested to DIN EN 50085-2-3. Base and cover in set.



**PVC** Polyvinylchloride

### Master data

Item number	6132355
Type	BEDIN 3737 sgr
Description 1	Slotted cable trunking system
Description 2	BE DIN Set 37,5x37,5 7030
Manufacturer	OBO
Colour	Stone grey; RAL 7030
Material	Polyvinylchloride
Smallest sales unit	80
Unit of quantity	Metre
Weight	27.85 kg
Weight unit	kg/100 m

### Dimensions

Length	2,000 mm
Width	38 mm
Height	38 mm

# Technical data sheet

Wiring trunking BE-DIN 37.5, trunking width 37.5

Item number: 6132355



## Technical data

Side wall version	Slotted
Fastening type	Base perforation
Flexible	no
Halogen-free	no
Creepage current-resistant	yes
With cover	yes
Usable cross-section	7.3 cm <sup>2</sup>
Slot spacing	10 mm
Slot width	4 mm
Self-extinguishing	yes